

Front wheel size	200 x 50mm;
Rear wheel size	200 x 65mm;
Ground clearance	50mm;
Length	1010mm;
Width	570mm;
Weight (without seat)	10kg (front-frame); 9.8kg (back frame);
Weight of seat	7.7kg (17lbs incl. frame & arm rest);
Max user weight	125kg (20 stone) on level ground;
Turn radius	910mm;
Motor output	2-150 Watt;
Transmission	Worm drive gearbox;
Reverse	Forward/reverse switch;
Brakes	Dynamic braking and electromagnetic break;
Battery (SLA)	24V - 15 ah (9.2kg);
Battery (Lithium)	24V - 15 ah (4.0kg);
Charger (SLA battery)	24 volt 2 amp;
Charger (Lithium battery)	On/off board 24 volt 4 amp - 0.9kg;
Max speed	6.5 kph / 4 mph; 3.9 kph / 2.4mph (2nd speed choice);
Slope grade ability	9 degrees with 120kg load. 12 degrees with 100kg load;
Travel distance	Up to 16km (10 miles) with standard SLA battery; Up to 20km (12.4 miles) with 15ah lithium battery;
Arm rests (optional)	Padded, flip back, removable; Distance between armrests 45cm - 55cm (18-22").